Amdt. dated December 29, 2008

Reply to Notice of Non-Compliant Amendment mailed October 22, 2008 and

Office action of February 15, 2008

In the Claims:

Claims 15, 17, 25 and 26 are amended herein. Claims 16 and 13 are canceled. The remaining claims are not amended.

1-14 (canceled)

15. (currently amended) A process for preparing a micropillar structure, characterized in that a solution having a polymer dissolved in a hydrophobic organic solvent is cast on a substrate, said organic solvent is evaporated in a moist atmosphere of relative humidity of 50% or higher to condense moisture contained in an atmosphere prevailing on a surface of said cast solution into micro-droplets, said micro-droplets are dispersed on the surface of said cast solution or in said cast solution into a close-packed packed structure, said microdroplets, condensed and dispersed on the surface of said cast solution or in said cast solution, are evaporated to obtain a porous honeycomb structure with said droplets used as casts, and said porous honeycomb structure is at least bisected by peeling in a thickness direction, thereby obtaining honeycomb structures wherein micro-pillars are regularly formed and arranged by said bisection on peeled sections, characterized in that said polymer is composed of a hydrophobic or biodegradable polymer and an amphipathic polymer and, optionally, a modifier is incorporated

Amdt. dated December 29, 2008

Reply to Notice of Non-Compliant Amendment mailed October 22, 2008 and

Office action of February 15, 2008

and said hydrophobic or biodegradable polymer comprises a polymer having a a poly(meth)acrylate, or a polystyrene as a basic skeleton.

- 16. (canceled)
- 17. (currently amended) A process for preparing a micropillar structure according to claim 16, wherein said polymer comprises 50 to 99% of said hydrophobic polymer and/or or said biodegradable polymer with the rest being said amphiphilic polymer.
 - 18. (canceled)
- 19. (original) A process for preparing a micro-pillar structure according to claim 15, wherein said moist atmosphere is adjusted to a relative humidity of 50 to 95%.
- 20. (original) A process for preparing a micro-pillar structure according to claim 15 or 19, characterized in that said atmosphere is an ordinary air atmosphere.
- 21. (original) A process for preparing a micro-pillar structure according to claim 15, characterized in that operation for evaporation of said organic solvent in said moist atmosphere is carried out by blowing an atmosphere having a high humidity onto an evaporation interface of said organic solvent.

Amdt. dated December 29, 2008

Reply to Notice of Non-Compliant Amendment mailed October 22, 2008 and Office action of February 15, 2008

- 22. (original) A process for preparing a micro-pillar structure according to claim 15, characterized in that peeling operation is carried out by use of an adhesive tape.
- 23. (withdrawn) A process for preparing a micro-pillar structure according to claim 15, characterized in that peeling operation is carried out by dissolution of the polymer.
- 24. (withdrawn) A process for preparing a micro-pillar structure according to claim 15, characterized in that peeling operation is carried out by ultrasonic irradiation.
- 25. (currently amended) A process for preparing a micropillar structure according to any one of claims 15 to [[24]] 17, 19 and 21-24, characterized in that said micro-pillars are arranged at a length of 0.1 to 50 μ m, a tip length of 0.01 to 20 μ m and a spacing of 0.1 to 100 μ m.
- 26. (currently amended) A process for preparing a micropillar structure according to any one of claims 15 to [[25]] 17, 19 and 21-24 above, wherein said micro-pillars are oriented in any direction except for a vertical direction and set with anisotropy.
- 27. (original) A process for preparing a micro-pillar structure according to claim 26, characterized in that said anisotropic micro-pillars are obtained by a peeling treatment

Amdt. dated December 29, 2008

Reply to Notice of Non-Compliant Amendment mailed October 22, 2008 and

Office action of February 15, 2008

with transverse shearing stress in such a way that when the porous honeycomb structure that is a micro-pillar precursor is sectioned by peeling in the thickness direction, the resulting micro-pillars are oriented in any direction except for the vertical direction.